



**TABLA SPECS  
TUBERIA PERFORACIÓN - DRILL PIPE**

Size in	Nominal Weight lb/ft	Wt in	Upset	Drill Pipe		Tool Joint							
				API SPEC 5D	Hilong Sour Service	API SPEC 7			HLDS			Pin Tong (in)	Box Tong (in)
						Conn.	OD Pin and Box(in)	ID PIN (in)	Conn.	OD Pin and Box(in)	ID PIN (in)		
2 3/8	6.65	0.28	EU	E		NC26	3 3/8	1 3/4	HLDS26	3 3/8	1 3/4	7	8
				X	HL95SS				HLDS26SS				
				G	HL105SS								
2 7/8	10.4	0.362	EU	E		NC31	4 1/8	2 1/8	HLDS31	4 1/8	2 1/8, 2 1/4	7	9
				X	HL95SS		HLDS31SS	4 1/8	2, 2 1/8				
				G	HL105SS		4 1/8	2	4 1/8	2, 2 1/8			
				S			4 3/8	1 5/8	4 3/8	1 5/8, 2			
3 1/2	13.3	0.368	EU	E		NC38	4 3/4	2 11/16	HLDS38	4 3/4	2 11/16, 2 13/16	8	10 1/2
				X	HL95SS		HLDS38SS	5	2 9/16, 2 11/16				
				G	HL105SS		5	2 7/16	5	2 7/16, 2 9/16			
				S			5	2 1/8	5	2 1/8, 2 1/2			
3 1/2	15.5	0.449	EU	E		NC38	5	2 9/16	HLDS38	5	2 9/16, 2 11/16	8	10 1/2
				X	HL95SS		HLDS38SS	5	2 7/16, 2 9/16				
				G	HL105SS		5	2 1/8	5	2 1/8, 2 1/2			
				S		NC40	5 1/2	2 1/4	HLDS40 HLDS40SS	5 1/2	2 1/4, 2 1/2	7	10









**TABLA SPECS  
TUBERIA PERFORACIÓN - DRILL PIPE**

Size in	Nominal Weight lb/ft	Wt in	Upset	Drill Pipe		Tool Joint							
				API SPEC 5D	Hilong Sour Service	API SPEC 7			HLDS			Pin Tong (in)	Box Tong (in)
						Conn.	OD Pin and Box(in)	ID PIN (in)	Conn.	OD Pin and Box(in)	ID PIN (in)		
			IEU	E		FH	7 1/4	3 1/2	HLDS26	7 1/4	3 1/2, 4	8	10
				X	HL95SS				HLDS512SS				
				G	HL105SS								
				S									
6 5/8	25.2 27.7	0.33 0.362	IEU	E		6 5/8 FH	8	5	HLDS658	8	5, 5 1/4	8	11
				X	HL95SS				HLDS658SS				
				G	HL105SS								
				S									
	IEU	E		6 5/8 FH	8	5	HLDS658	8	5, 5 1/4	8 1/4	4 3/4, 5	8	11
		X	HL95SS				HLDS658SS						
		G	HL105SS										
		S											

**Notes:**

1. The specifications of drill pipe joint can be determined based on user requirements, nevertheless its determination should ensure meeting requirements in anti-torque strength.
2. Drill pipe of other specifications are also available based on user requirements.